

KODAK PIXPRO FZ102

DIGITAL CAMERA



FZ102 FRIENDLY ZOOM

Introducing the FZ102 Friendly Zoom camera from the KODAK PIXPRO Digital Camera Collection. A compact, easy-to-use camera that goes beyond the basics, the FZ102 offers powerful zoom for its small stature as well as a variety of shooting modes, white balance control, and multiple language settings designed to streamline your capabilities behind the lens. KODAK PIXPRO Digital Cameras – Tell your story.

FEATURES:

- 10X Optical Zoom
- 25mm Wide Angle
- 16MP
- 2.7" LCD (230K Pixels)
- 720p HD Video
- Digital Image Stabilization
- Li-ion Battery

10X
OPTICAL
ZOOM

25mm
WIDE

16MP

2.7"
6.8cm

HD

**Panorama
Capture**



Available Colors:

- BLACK
- RED

Images are simulated.



KODAK PIXPRO FZ102

DIGITAL CAMERA

SPECIFICATIONS	FZ102
Effective Image Sensor Pixels	16.15 Megapixels
Total Image Sensor Pixels	16.44 Megapixels [1/2.3"(CCD)]
Lens	
Focal Length	4.5 mm (Wide) — 45 mm (Tele)
[35mm film equivalent]	[25 mm (Wide) — 250 mm (Tele)]
F number	F3.6 (Wide) — F6.7 (Tele)
Lens Construction	8 groups 8 elements
Optical Zoom	10x
Focusing Range	Normal: (Wide) 60cm — ∞, (Tele) 200 cm — ∞ Macro: 3 cm — ∞ (Wide Only)
Autofocus System	TTL Autofocus
Anti-Handshake	Digital Image Stabilization
Digital Zoom	6x Digital Zoom (Combined Zoom: 60x)
Number of Recording Pixels	
Still Image	(4:3) 16MP: 4608x3456, 10MP: 3648x2736, 5MP: 2592x1944, 3MP: 2048x1536, 0.3MP: 640x480, (3:2) 14MP: 4608x3072, (16:9) 12MP: 4608x2592, 2MP: 1920x1080
Movie	1280x720(30/15fps), 640x480(30fps)
Image Compression	Best, Fine, Normal
DCF, DPOF (Ver1.1) Support	Yes
File Format	
Still Image	Exif 2.3 (JPEG)
Movie	Movie Format: MOV (Motion JPEG), Audio: G.711 [Monaural]
Shooting Modes	M, Auto, Portrait, Movie, Panorama, SCN
SCN Modes	ASCN, Landscape, Sport, Beach, Sunset, Fireworks, Night Landscape, Sketch, Snow, Children, ID, Glass, Photo Frame, Panning Shot, Night Portrait, Fish Eye, Party, Indoor, Leaf, Museum, Image Stabilization
Detection Features	Face, Smile, Blink
Photo Touch-up	Red-Eye Removal, HDR
Panorama Capture	0° – 180° (Horizontal)
LCD Display	2.7 inch (230K Pixels)
ISO Sensitivity	Auto, ISO 80/100/200/400/800/1600
AF Method	Single AF, Multi-AF (TTL 9-point), Face Detection
Exposure Metering Method	Artificial Intelligence AE (AiAE), Center-Weighted Average, Spot (Fixed to Center of Frame), Face AE
Exposure Control Method	Program AE (AE-Lock Available)
Exposure Compensation	+/- 2EV in 1/3 Step Increments
Shutter Speed	1/2000 – 4 Seconds (Manual: 30 Seconds)
Continuous Shooting	Yes
Playback Modes	Single, Index (9/16 Thumbnails) Slide Show, Zoom (Approx. x2 – x8)
White Balance Control	Auto (AWB), Daylight, Cloudy, Fluorescent, Fluorescent CWF, Incandescent, Manual
Flash	
Flash Method	Pop-up (Manual)
Flash Modes	Auto, Red-Eye Reduction, Fill Flash, Slow Synchro, Red-Eye Reduction + Slow Synchro, Force Off
Shooting Range	(Wide) Approx. 0.5 m – 4.3 m (ISO800); (Tele) Approx. 2.0 m – 2.3 m (ISO800)
Recording Media	Internal Memory: Approx. 8MB SD/SDHC Card (Up to 32GB Support) [MMC Card not supported]
Other Features	Multi-Language Support (27 Languages)
Jacks	AV-OUT/USB 2.0 (Micro 5-pin USB)
Power	Rechargeable Li-ion Battery LB-052, 3.7V 890mAh, In-Camera Charging
Shooting Capability (Battery Performance)	Approx. 210 Shots (Based on CIPA Standards)
Operation Environment	Temperature: 32° – 104°F / 0° – 40°C, Humidity: 0 – 90%
Dimensions (WxHxD)	Approx. 4.46 x 2.91 x 1.76 in. / 113.3 x 74.0 x 44.8 mm (Based on CIPA Standards)
Weight	Approx. 7.3 oz. / 208g (Body Only)
Supplied Accessories	Rechargeable Li-ion Battery, USB Cable, AC Adapter, Wrist Strap, Quick Start Guide, Warranty Card, Service Card

JK Imaging Ltd.

17239 So. Main Street, Gardena, CA 90248
(888) 978-0806

To learn more about KODAK PIXPRO Digital Cameras:
visit: kodakpixpro.com

© 2018 JK Imaging, Ltd. The Kodak trademark, logo and trade dress are used under license from Eastman Kodak Company.
All information contained in this document is subject to change without notice. Document Number/Sequence: U.DIS.0052.1217.en.03

