

Kodak PIXPRO

Digital Devices

SL10 SMART LENS® CAMERA



FEATURES:

Your smart phone just got a whole lot better. Introducing the new KODAK PIXPRO SL10 SMART LENS® camera. 10x mega zoom, highly portable and easy to attach to your smart phone, for photos and video that have never looked this good. And if that isn't enough, the SL10 is wireless so you have even more flexibility to use it with or without your phone and upload your favorite shots to your social media streams. KODAK PIXPRO SMART LENS - Tell your story.

- 16MP BSI CMOS sensor
- 10X Optical Zoom
- 28mm Wide Angle
- Full HD 1080p Video
- 6fps Burst Shooting
- Optical Image Stabilization
- Wi-Fi / NFC Compatible
- Wirelessly Connect / Control with Smart Devices



Available Colors:



Kodak

PIXPRO SL10

Digital Device



SPECIFICATIONS

SL10

Effective Image Sensor Pixels	16.35 Megapixels
Total Image Sensor Pixels	16.76 Megapixels [1/2.3" BSI CMOS]
Lens	
Focal Length	5.0 mm (Wide) — 50.0 mm (Tele)
[35mm film equivalent]	[28 mm (Wide) — 280 mm (Tele)]
F number	F3.2 (Wide) — F5.6 (Tele)
Lens Construction	8 groups 12 elements
Optical Zoom	10x
Focusing Range	Normal: (Wide) 60cm — ∞, (Tele) 100 cm — ∞ Macro: 5 cm — ∞ (Wide Only)
Autofocus System	TTL Autofocus
Anti-Handshake	Optical Image Stabilization
Number of Recording Pixels	
Still Image	(4:3) 16MP: 4608x3456, 10MP: 3648x2736, (16:9) 12MP: 4608x2592, 2MP: 1920x1080
Movie	1920x1080-30fps, 1280x720-30fps; High-Speed Movie: 848x480-120 fps
File Format	
Still Image	Exif 2.3 (JPEG)
Movie	MP4 [Image: H.264; Audio: AAC (Stereo)]
Shooting Modes	P, Face Beautifier, ASCN, HDR, Burst Shooting, Low Light (WDR), Movie
ISO Sensitivity	Auto, ISO 100/200/400/800/1600/3200
AF Method	Single AF, Touch
Exposure Metering Method	Artificial Intelligence AE (AiAE)
Exposure Control Method	Program AE (AE-Lock Available)
Exposure Compensation	± 3EV in 1/3 Step Increments
Shutter	
Type	Mechanical Shutter and Electronic Shutter
Speed	1/2000 – 4 Seconds
Continuous Shooting	Approx. 6fps (Full Resolution)
White Balance Control	Auto (AWB), Daylight, Cloudy, Fluorescent, Fluorescent CWF, Incandescent
Recording Media	Micro SD/Micro SDHC Card (Min. 4GB up to 32GB Max. Support) [MMC Card Not Supported]
Jacks	USB 2.0 (Micro 5 pin USB)
Wi-Fi	Yes (802.11 b/g/n)
NFC	Yes
Remote Control	Yes (via Smart Device)
Power	Rechargeable Li-ion Battery LB-052, 3.7V 880mAh, In-Camera Charging
Shooting Capability (Battery Performance)	Approx. 200 Shots (Based on CIPA Standards)
Operation Environment	Temperature: 8° - 104°F / 0° - 40°C, Humidity: 0 - 90%
Dimensions (WxHxD)	Approx. 2.35 x 2.35 x 2.20 in / 59.6 x 59.6 x 55.8 mm (Based on CIPA Standards)
Weight	Approx. 5.12 oz. / 145 g (Body Only)
Supplied Accessories	Rechargeable Li-ion Battery, AC Adapter, Wrist Strap, USB Cable, Quick Start Guide, User Manual, Service Card, Warranty Card
Compatible Devices	iPhone® 4/4s/5/5c/5s (iOS 6.0 and up) iPad® 1st - 4th generation (iOS 6.0 and up) iPod Touch® 4th generation (iOS 6.0 and up) Android® phones (version 2.3 and up) Android® tablets (version 3.0 and up)

JK Imaging Ltd.

JK Imaging, Ltd.
1411 W. 190th Street, Suite 550
Gardena, CA 90248

To learn more about KODAK PIXPRO Digital Cameras:
visit: www.kodakpixpro.com

