**KODAK PIXPRO AZ421** 

DIGITAL CAMERA



## **AZ421 ASTRO ZOOM**

Passion and performance go hand in hand with our KODAK PIXPRO AZ421 digital camera from the Astro Zoom Collection. A 42x ultra long zoom lens with optical image stabilization delivers crisp, clear 16 megapixel close-ups, panorama or HD videos. Auto scene, object tracking, post-editing features and a host of powerful yet user-friendly settings make photography easy, fun and zero hassle. KODAK PIXPRO Digital Cameras - Tell your story.

### **FEATURES:**

- 42X Optical Zoom
- 24mm Wide Angle
- 16 Megapixels
- 3" LCD (460K Pixels)
- 720p HD Video
- OIS (Optical Image Stabilization)
- Li-ion Battery















Available Colors:

**BLACK** 

RED

WHITE



# **KODAK PIXPRO AZ421**

## DIGITAL CAMERA

| SPECIFICATIONS   | AZ421   |
|--|---|
|  |   |
| Effective Image Sensor Pixels  | 16.15 Megapixels  |
| Total Image Sensor Pixels  | 16.44 Megapixels [1/2.3"(CCD)]  |
| Lens<br>Focal Length   | 4.3 mm (Wide) — 180.6 mm (Tele)   |
| [ 35mm film equivalent ]   | [24 mm (Wide) — 1008 mm (Tele)]   |
| F number   | F3.0 (Wide) — F6.8 (Tele)   |
| Lens Construction  | 11 groups 15 elements   |
| Optical Zoom   | 42x   |
| Focusing Range   | Normal: (Wide) 50 cm $-\infty$ , (Tele) 200 cm $-\infty$<br>Macro: 1.6 cm $-\infty$ (Wide Only)   |
| Autofocus System   | TTL Autofocus   |
| Anti-Handshake   | Optical Image Stabilization   |
| Digital Zoom   | 4x Digital Zoom (Combined Zoom: 168x)   |
| Number of Recording Pixels   |   |
| Still Image  | (4:3) 16MP: 4608x3456, 10MP: 3648x2736, 5MP: 2592x1944, 3MP: 2048x1536, 0.3MP: 640x480, (3:2) 14MP: 4608x3072, (16:9) 12MP: 4608x2592, 2MP: 1920x1080   |
| Movie  | 1280x720: 30fps / 15fps, 640x480: 30fps   |
| Image Compression  | Best, Fine, Normal  |
| DCF, DPOF (Ver1.1) Support   | Yes   |
| File Format  | 5 (00 (050)   |
| Still Image  | Exif 2.3 (JPEG)   |
| Movie  | MOV [Image: H.264; Audio: Linear PCM (Monaural)]  |
| Shooting Modes   | Auto, P, S, A, M, Face Beautifier, Panorama, Movie, CS, SCN [ASCN, Landscape, Sport, Sunset, Fireworks, Night Landscape, Snow, Children, Portrait, Party, Night Portrait, Pet]  |
| Detection Features   | Face, Smile, Blink, Cat, Dog  |
| Photo Touch-up   | Red-Eye Removal, Skin Soften, Eye Brightening, Eye Enlargement  |
| HDR  | Yes   |
| Panorama   | Up to 180° (Horizontal)   |
| LCD Display  | 3.0 inch (460K Pixels)  |
| ISO Sensitivity  | Auto, ISO 80/100/200/400/800/1600/3200 (4M)   |
| AF Method  | Single AF, Multi-AF (TTL 9-point), Object Tracking, Face Detection  |
| Exposure Metering Method   | Artificial Intelligence AE (AiAE), Center-Weighted Average, Spot (Fixed to Center of Frame), Face AE  |
| Exposure Compensation  | +/- 2EV in 1/3 Step Increments  |
| Shutter Speed  | 1/2000 ~ 30 Seconds   |
| Continuous Shooting  | Yes   |
| Playback Modes   | Single Photo, Index (9/16 Thumbnails), Slide Show, Date, Zoom (Approx. x2 ~ x8)   |
| White Balance Control  | Auto (AWB), Daylight, Cloudy, Fluorescent, Fluorescent CWF, Incandescent, Manual, Color Temperature   |
|  | Setting (1900K - 10000K)  |
| Flash  |   |
| Flash Method   | Pop-up (Manual)   |
| Flash Method<br>Flash Modes  | Pop-up (Manual) Auto, Red-Eye Reduction, Fill Flash, Slow Synchro, Red-Eye Reduction + Slow Synchro, Forced Off   |
| Flash Method   | Pop-up (Manual) Auto, Red-Eye Reduction, Fill Flash, Slow Synchro, Red-Eye Reduction + Slow Synchro, Forced Off (Wide) Approx. 0.5 m – 7.5 m (ISO800); (Tele) Approx. 1.2 m – 3.7 m (ISO800) Internal Memory: Approx. 8MB   |
| Flash Method<br>Flash Modes<br>Shooting Range<br>Recording Media   | Pop-up (Manual) Auto, Red-Eye Reduction, Fill Flash, Slow Synchro, Red-Eye Reduction + Slow Synchro, Forced Off (Wide) Approx. 0.5 m – 7.5 m (ISO800); (Tele) Approx. 1.2 m – 3.7 m (ISO800) Internal Memory: Approx. 8MB SD/SDHC Card (Up to 32GB Support) [MMC Card Not Supported]  |
| Flash Method<br>Flash Modes<br>Shooting Range<br>Recording Media<br>Other Features   | Pop-up (Manual) Auto, Red-Eye Reduction, Fill Flash, Slow Synchro, Red-Eye Reduction + Slow Synchro, Forced Off (Wide) Approx. 0.5 m – 7.5 m (ISO800); (Tele) Approx. 1.2 m – 3.7 m (ISO800) Internal Memory: Approx. 8MB SD/SDHC Card (Up to 32GB Support) [MMC Card Not Supported] Eye-Fi* Compatible, PictBridge, ExifPrint Support, Multi-Language Support (27 Languages)   |
| Flash Method<br>Flash Modes<br>Shooting Range<br>Recording Media<br>Other Features<br>Jacks  | Pop-up (Manual) Auto, Red-Eye Reduction, Fill Flash, Slow Synchro, Red-Eye Reduction + Slow Synchro, Forced Off (Wide) Approx. 0.5 m - 7.5 m (ISO800); (Tele) Approx. 1.2 m - 3.7 m (ISO800) Internal Memory: Approx. 8MB SD/SDHC Card (Up to 32GB Support) [MMC Card Not Supported] Eye-Fi* Compatible, PictBridge, ExifPrint Support, Multi-Language Support (27 Languages) AV-OUT/USB 2.0 (Micro 5 pin USB), HDMI (Type D)   |
| Flash Method Flash Modes Shooting Range Recording Media Other Features Jacks Power   | Pop-up (Manual) Auto, Red-Eye Reduction, Fill Flash, Slow Synchro, Red-Eye Reduction + Slow Synchro, Forced Off (Wide) Approx. 0.5 m - 7.5 m (ISO800); (Tele) Approx. 1.2 m - 3.7 m (ISO800) Internal Memory: Approx. 8MB SD/SDHC Card (Up to 32GB Support) [MMC Card Not Supported] Eye-Fi* Compatible, PictBridge, ExifPrint Support, Multi-Language Support (27 Languages) AV-OUT/USB 2.0 (Micro 5 pin USB), HDMI (Type D) Rechargeable Li-ion Battery LB-060, 3.7V 1100mAh, In-Camera Charging  |
| Flash Method Flash Modes Shooting Range Recording Media  Other Features Jacks Power Shooting Capability (Battery Performance)  | Pop-up (Manual) Auto, Red-Eye Reduction, Fill Flash, Slow Synchro, Red-Eye Reduction + Slow Synchro, Forced Off (Wide) Approx. 0.5 m – 7.5 m (ISO800); (Tele) Approx. 1.2 m – 3.7 m (ISO800) Internal Memory: Approx. 8MB SD/SDHC Card (Up to 32GB Support) [MMC Card Not Supported] Eye-Fi* Compatible, PictBridge, ExifPrint Support, Multi-Language Support (27 Languages) AV-OUT/USB 2.0 (Micro 5 pin USB), HDMI (Type D) Rechargeable Li-ion Battery LB-060, 3.7V 1100mAh, In-Camera Charging Approx. 200 Shots (Based on CIPA Standards)  |
| Flash Method Flash Modes Shooting Range Recording Media  Other Features Jacks Power Shooting Capability (Battery Performance) Operation Environment                    | Pop-up (Manual) Auto, Red-Eye Reduction, Fill Flash, Slow Synchro, Red-Eye Reduction + Slow Synchro, Forced Off (Wide) Approx. 0.5 m - 7.5 m (ISO800); (Tele) Approx. 1.2 m - 3.7 m (ISO800) Internal Memory: Approx. 8MB SD/SDHC Card (Up to 32GB Support) [MMC Card Not Supported] Eye-Fi* Compatible, PictBridge, ExifPrint Support, Multi-Language Support (27 Languages) AV-OUT/USB 2.0 (Micro 5 pin USB), HDMI (Type D) Rechargeable Li-ion Battery LB-060, 3.7V 1100mAh, In-Camera Charging Approx. 200 Shots (Based on CIPA Standards)  Temperature: 32° – 104°F / 0° – 40°C, Humidity: 0 – 90%   |
| Flash Method Flash Modes Shooting Range Recording Media  Other Features Jacks Power Shooting Capability (Battery Performance) Operation Environment Dimensions (WxHxD) | Pop-up (Manual) Auto, Red-Eye Reduction, Fill Flash, Slow Synchro, Red-Eye Reduction + Slow Synchro, Forced Off (Wide) Approx. 0.5 m – 7.5 m (ISO800); (Tele) Approx. 1.2 m – 3.7 m (ISO800) Internal Memory: Approx. 8MB SD/SDHC Card (Up to 32GB Support) [MMC Card Not Supported] Eye-Fi* Compatible, PictBridge, ExifPrint Support, Multi-Language Support (27 Languages) AV-OUT/USB 2.0 (Micro 5 pin USB), HDMI (Type D) Rechargeable Li-ion Battery LB-060, 3.7V 1100mAh, In-Camera Charging Approx. 200 Shots (Based on CIPA Standards)  Temperature: 32° – 104°F / 0° – 40°C, Humidity: 0 – 90% Approx. 4.44 x 3.21 x 3.32 in. / 112.7 x 81.6 x 84.4 mm (Based on CIPA Standards) |
| Flash Method Flash Modes Shooting Range Recording Media  Other Features Jacks Power Shooting Capability (Battery Performance) Operation Environment                    | Pop-up (Manual) Auto, Red-Eye Reduction, Fill Flash, Slow Synchro, Red-Eye Reduction + Slow Synchro, Forced Off (Wide) Approx. 0.5 m – 7.5 m (ISO800); (Tele) Approx. 1.2 m – 3.7 m (ISO800) Internal Memory: Approx. 8MB SD/SDHC Card (Up to 32GB Support) [MMC Card Not Supported] Eye-Fi* Compatible, PictBridge, ExifPrint Support, Multi-Language Support (27 Languages) AV-OUT/USB 2.0 (Micro 5 pin USB), HDMI (Type D) Rechargeable Li-ion Battery LB-060, 3.7V 1100mAh, In-Camera Charging Approx. 200 Shots (Based on CIPA Standards)  Temperature: 32° – 104°F / 0° – 40°C, Humidity: 0 – 90%   |

## JK Imaging Ltd.

17239 So. Main Street, Gardena, CA 90248 (888) 978-0806

© 2020 JK Imaging, Ltd. The Kodak trademark, logo and trade dress are used under license from Eastman Kodak Company. All information contained in this document is subject to change without notice. Document Number/Sequence: U.DIS.0018.0819.en.05

To learn more about KODAK PIXPRO Digital Cameras:

visit: kodakpixpro.com











