KODAK PIXPRO FZ152

DIGITAL CAMERA



FZ152 FRIENDLY ZOOM

If you're looking for a powerful, compact camera that captures life's special moments, then look no further. The FZ152 has 15X zoom, over 25 shooting modes and a wide angle lens that captures more out of every shot. One button 720p HD video makes this portable camera even more powerful and a breeze to use. KODAK PIXPRO Digital Cameras – Tell your story.

FEATURES:

- 15X Optical Zoom
- 24mm Wide Angle
- 16MP
- 3" LCD (230K Pixels)
- 720p HD Video
- OIS (Optical Image Stabilization)
- Li-ion Battery















Available Colors:

BLACK

RED



KODAK PIXPRO FZ152

DIGITAL CAMERA

SPECIFICATIONS	FZ152
Effective Image Sensor Pixels	16.15 Megapixels
Total Image Sensor Pixels	16.44 Megapixels [1/2.3"(CCD)]
Lens Focal Length [35mm film equivalent] F number Lens Construction Optical Zoom Focusing Range	4.3 mm (Wide) — 64.5 mm (Tele) [24 mm (Wide) — 360 mm (Tele)] F3.3 (Wide) — F5.9 (Tele) 9 groups 10 elements 15x Normal: (Wide) 60cm — ∞, (Tele) 250 cm — ∞ Macro: 3 cm —∞ (Wide Only)
Anti-Handshake	OIS (Optical Image Stabilization)
Digital Zoom	4x Digital Zoom (Combined Zoom: 60x)
Number of Recording Pixels Still Image Movie	(4:3) 16MP: 4608x3456, 10MP: 3648x2736, 5MP: 2592x1944, 3MP: 2048x1536, 0.3MP: 640x480, (3:2) 14MP: 4608x3072, (16:9) 12MP: 4608x2592, 2MP: 1920x1080 1280x720(30/15fps), 640x480(30fps)
Image Compression DCF, DPOF (Ver1.1) Support	Best, Fine, Normal Yes
File Format	ies
Still Image	Exif 2.3 (JPEG)
Movie	MOV [Image: Motion JPEG; Audio: G.711(Monaural)]
Shooting Modes	M, Auto, Portrait, Movie, Panorama, SCN
SCN Modes	ASCN, Landscape, Sport, Beach, Sunset, Fireworks, Night Landscape, Sketch, Snow, Children, ID, Glass, Photo Frame, Panning Shot, Fish Eye, Party, Indoor, Leaf, Museum, Night Portrait)
Detection Features	Face, Smile, Blink
Photo Touch-up	Red-Eye Removal, HDR
Panorama Capture	0° – 180° (Horizontal)
LCD Display	3.0 inch (230K Pixels)
ISO Sensitivity	Auto, ISO 80/100/200/400/800/1600
AF Method	Single AF, Multi-AF (TTL 9-point), Face Detection
Exposure Metering Method	Artificial Intelligence AE (AiAE), Center-Weighted Average, Spot (Fixed to Center of Frame), Face AE
Exposure Control Method	Program AE (AE-Lock Available)
Exposure Compensation	+/- 2EV in 1/3 Step Increments
Shutter Speed	1/2000 - 4 Seconds (Manual: 30 Seconds)
Continuous Shooting	Yes
Playback Modes	Single Photo, Index (9/16 Thumbnails) Slide Show, Zoom (Approx. x2 - x8)
White Balance Control	Auto (AWB), Daylight, Cloudy, Flourescent, Flourescent CWF, Incandescent, Manual
Flash Flash Method Flash Modes Shooting Range	Pop-up (Manual) Auto, Red-Eye Reduction, Fill Flash, Slow Synchro, Red-Eye Reduction + Slow Synchro, Force Off (Wide) Approx. 0.5 m - 4.7 m (ISO800); (Tele) Approx. 1.0 m - 2.6 m (ISO800)
Recording Media	Internal Memory: Approx. 8MB SD/SDHC Card (Up to 32GB Support) [MMC Card not supported]
Other Features	Eye-Fi, Multi-Language Support (27 Languages)
Jacks	AV-OUT/USB 2.0 (Micro 5-pin USB)
Power	Rechargeable Li-ion Battery LB-052, 3.7V 890mAh, In-Camera Charging
Shooting Capability (Battery Performance)	Approx. 210 Shots (Based on CIPA Standards)
Operation Environment	Temperature: 32° – 104°F / 0° – 40°C, Humidity: 0 – 90%
Dimensions (WxHxD)	Approx. 4.27 x 2.76 x 1.31 in. / 108.4 x 69.9 x 33.5 mm (Based on CIPA Standards)
Weight	Approx. 6.5 oz. / 185g (Body Only)
Supplied Accessories	Rechargeable Li-ion Battery, USB Cable, AC Adapter, Wrist Strap, Quick Start Guide, Warranty Card, Service Card

JK Imaging Ltd.

17239 So. Main Street, Gardena, CA 90248 (888) 978-0806

© 2021 JK Imaging, Ltd. The Kodak trademark, logo and trade dress are used under license from Eastman Kodak Company. All information contained in this document is subject to change without notice. Document Number/Sequence: U.DIS.0031.0321.en.08

To learn more about KODAK PIXPRO Digital Cameras:

visit: kodakpixpro.com











