Kodak **PIXPRO Digital Cameras**

FRIENDLY ZOOM FZ201

FEATURES:

Who doesn't want an all-in-one well versed travel companion? Our KODAK PIXPRO FZ201 Friendly Zoom compact camera is just that. With an impressive 20x optical zoom, you'll get close enough to feel like you're right in the thick of the action without leaving your post. One-touch HD video, easily-accessible feature buttons and a slim and smooth body design makes the FZ201 a perfect camera to go anywhere you go. KODAK PIXPRO Digital Cameras. Tell your story.

- 20X Optical Zoom
- 25mm Wide Angle
- 16 Megapixels
- 3" LCD
- 720p HD Video
- Optical Image Stabilization
- Li-ion Battery



Available Colors:









Kodak PIXPRO FZ201

20X 25 OPTICAL 25

25mm WIDE





Digital Camera

SPECIFICATIONS	FZ201
Effective Image Sensor Pixels	16.15 Megapixels
Total Image Sensor Pixels	16.44 Megapixels [1/2.3"(CCD)]
Lens	
Focal Length	4.5 mm (Wide) – 90.0 mm (Tele)
[35mm film equivalent]	[25 mm (Wide) — 500 mm (Tele)]
F number	F3.5 (Wide) – F4.9 (Tele)
Lens Construction	9 groups 11 elements
Optical Zoom	20x
Focusing Range	Normal: (Wide) 60cm — ∞, (Tele) 200 cm — ∞ Macro: 3 cm —∞ (Wide Only)
Anti-Handshake	Optical Image Stabilization
Digital Zoom	4x Digital Zoom (Combined Zoom: 80x)
Number of Recording Pixels	
Still Image	(4:3) 16MP: 4608x3456, 10MP: 3648x2736, 5MP: 2592x1944, 3MP: 2048x1536, 0.3MP: 640x480, (3:2) 14MP: 4608x3072, (16:9) 12MP: 4608x2592, 2MP: 1920x1080
Movie	1280x720 (30/15fps), 640x480 (30fps)
Image Compression	Best, Fine, Normal
DCF, DPOF (Ver1.1) Support	Yes
File Format	
Still Image	Exif 2.3 (JPEG)
Movie	MOV [Image: Motion JPEG; Audio: G.711 (Monaural)]
Shooting Modes	Auto, Manual, Portrait, Movie, Panorama, Scene [ASCN, Landscape, Sport, Beach, Sunset, Fireworks, Night Landscape, Snow, Childre ID, Glass, Photo Frame, Panning Shot, Night Portrait, Fish Eye, Party, Indoor, Leaf, Museum , Night Portrait, Sketch]
Detection Features	Face, Smile, Blink, Cat, Dog
Photo Touch-up	Red-Eye Removal, High Dynamic Range (HDR)
Panorama Capture	0° - 180° (Horizontal)
LCD Display	3.0 inch (230K Pixels)
ISO Sensitivity	Auto, ISO 80/100/200/400/800/1600
AF Method	Single AF, Multi-AF (TTL 9-point), Face Detection
Exposure Metering Method	Artificial Intelligence AE (AiAE), Center-Weighted Average, Spot (Fixed to Center of Frame), Face AE
Exposure Control Method	Program AE (AE-Lock Available)
Exposure Compensation	+/- 2EV in 1/3 Step Increments
Shutter Speed	1/2000 - 4 Seconds (Manual: 30 Seconds)
Continuous Shooting	Yes
Playback Modes	Single Photo, Index (9/16 Thumbnails) Slide Show, Date, Zoom (Approx. x2 - x8)
White Balance Control	Auto (AWB), Daylight, Cloudy, Flourescent, Flourescent CWF, Incandescent, Manual
Flash	
Flash Method Flash Modes	Pop-Up (Manual) Auto, Red-Eye Reduction, Fill Flash, Force Off, Slow Synchro, Red-Eye Reduction + Slow Synchro
Shooting Range Recording Media	(Wide) Approx. 0.5 m - 4.5 m (ISO800); (Tele) Approx. 1.2 m - 3.2 m (ISO800) Internal Memory: Approx. 8MB
	SD/SDHC Card (Up to 32GB Support) [MMC Card not supported]
Other Features	PictBridge, ExifPrint Support, Eye-Fi® Compatible, Multi-Language Support (27 Languages)
Jacks	AV-OUT/USB 2.0 (Micro 5-pin USB)
Power	Rechargeable Li-ion Battery LB-050, 3.7V 900mAh, In-Camera Charging
Shooting Capability (Battery Performance)	Approx. 210 Shots (Based on CIPA Standards)
Operation Environment	Temperature: 32° - 104°F / 0° - 40°C, Humidity: 0 - 90%
Dimensions (WxHxD)	Approx. 4.32 x 2.74 x 1.51 / 109.7 x 69.6 x 38.3 mm (Based on CIPA Standards)
Weight	Approx. 7.13 oz / 202 g (Body Only)
Supplied Accessories	Rechargeable Li-ion Battery, AC Adapter, USB Cable, Neck Strap, Service Card, Quick Start Guide, Warranty Card

JK Imaging Ltd.

JK Imaging, Ltd. 1411 W. 190th Street, Suite 550 Gardena, CA 90248 To learn more about KODAK PIXPRO Digital Cameras: visit: **www.kodakpixpro.com**



© 2014 JK Imaging, Ltd. The Kodak trademark and trade dress are used under license from Kodak. All information contained in this document is subject to change without notice. Document Number/Sequence: U.DIS.0017.1110.en.02

