

KODAK PIXPRO P1

DIGITAL CAMERA



P1 ACTION SPORT

Capture every adventure with the new KODAK PIXPRO P1. Designed for life on the go, this compact and waterproof camera combines easy-to-use features and a convenient flip-up LCD screen for selfies. High-quality photo and video performance makes this camera the perfect companion for travel, outdoor activities, family fun, and everyday memories.

KODAK PIXPRO Digital Cameras - Tell Your Story.

FEATURES:

- 13MP CMOS Sensor
- 26mm, F2.0 Fixed Focus Lens
- 2.8" (920K) 180° Tilt LCD
- Waterproof/Shockproof/Dustproof
- 3 color Ring Light
- 1080p Full HD Video
- Built-in Li-ion Battery



Images are simulated.

Available Colors:

- GUNMETAL/BLACK
- GUNMETAL/WHITE
- AQUA/WHITE



KODAK PIXPRO P1

DIGITAL CAMERA

SPECIFICATIONS	P1
Effective Image Sensor Pixels	13 Megapixels
Total Image Sensor Pixels	13 Megapixels [1/3" BSI CMOS]
Lens	
Focal Length	3.57 mm
[35mm film equivalent]	26 mm
F number	F2.0
Lens Construction	5 elements
Optical Zoom	Fix Focus
Focusing Range	Normal: 60 cm — ∞ Macro: 8 cm — ∞
Autofocus System	TTL Autofocus
Digital Zoom	4x Digital Zoom
Number of Recording Pixels	
Still Image	(4:3) 13MP: 4160x3120, 5MP: 2592x1944, (16:9) 10MP: 4160x2340, 2MP: 1920x1080
Movie	1920x1080: 60fps / 30fps, 1280x720: 60fps / 30fps
Image Compression	Best, Fine
DCF Support	Yes
File Format	
Still Image	Exif 2.2 (JPEG)
Movie	MOV [Image: H.264; Audio: Linear PCM (Monaural)]
Shooting Modes	Auto, P, Portrait, Night, Landscape, Movie, Backlight, Beach, Children, Underwater
Waterproof	Up to 5m
Shockproof	Up to 1m
Dustproof	Equivalent to JIS/IEC (IP6X)
LCD Display	2.8 inch (920k Pixels)
Touch Panel	No
Angle Adjustment	Tilt (upwards approx. 180°)
G-Sensor	Yes
ISO Sensitivity	Auto ISO 100/200/400/800/1600
AF Method	Single AF
Exposure Metering Method	Average Metering, Spot (Fixed to Center of Frame), Center-Weighted Metering
Exposure Control Method	Program AE (AE-Lock Available)
Exposure Compensation	+/- 2EV in 1/3 Step Increments
Shutter Speed	1/10000 ~ 2 Seconds
Continuous Shooting	Yes
Playback Modes	Single, Index (9 Thumbnails), Zoom (Approx. ×2 ~ ×4)
White Balance Control	Auto (AWB), Daylight, Cloudy, Fluorescent, Fluorescent CWF, Incandescent, Underwater
LED Flash	
Flash Method	Internal
Flash Modes	Flash Auto, Force Flash, Force Off
Fill Light Ring	Cool White Light (7100K), White Light (5300K), Warm Light (2500K)
Recording Media	microSD/microSDHC/microSDXC Card (Up to 1.5TB Support) [MMC Card Not Supported]
Multi-Language Support (27)	English, Chinese (Simplified and Traditional), Japanese, Korean, French, Spanish, Portuguese, Thai, Indonesia, Vietnamese, Italian, German, Dutch, Russian, Polish, Swedish, Danish, Finnish, Norwegian, Greek, Turkish, Hungarian, Croatian, Czech, Arabic, Hindi
Jacks	USB 2.0 (Type-C)
Power	Built-in Li-ion Battery, 3.7V 700mAh, In-Camera Charging
Battery Charging Time	Approx. 2.5 Hours (Use AC Adapter and Battery is Exhausted)
Shooting Capability (Battery Performance)	Approx. 200 Shots (Based on CIPA Standards) Approx. 1h 30min for Video (@1080/30fps)
Operation Environment	Temperature: 32° ~ 104°F / 0° ~ 40°C, Humidity: 0 ~ 90%
Dimensions (WxHxD)	Approx. 4.15 × 2.48 × 0.89 in. / 105.5 × 63 × 22.5mm (Based on CIPA Standards)
Weight	Approx. 4.76 oz. / 135g (Body Only)
Supplied Accessories	Type-C USB Cable, AC Adapter, Wrist Strap, Quick Start Guide, Warranty Card, Service card

¹ Use Class 10 Card or Better

² SPEC For US

JK Imaging Ltd.

14067 Stage Road, Santa Fe Springs, CA 90670
(888) 978-0806

© 2026 JK Imaging, Ltd. The Kodak trademark, logo and trade dress are used under license from Eastman Kodak Company.
All information contained in this document is subject to change without notice. Document Number/Sequence: U.DIS.20260914.en.02

To learn more about KODAK PIXPRO Digital Cameras:
visit: kodakpixpro.com

