## KODAK PIXPRO AZ251 DIGITAL CAMERA



# **AZ251 ASTRO ZOOM**

Meet the KODAK PIXPRO AZ251 Astro Zoom camera the perfect entry-level mega zoom bridge camera to transform you into a photographer. With powerful features such as a 16MP CCD sensor, 25x zoom, and 24mm super wide-angle lens, you won't be surprised by the beautiful photos, but you might be by the small price tag. KODAK PIXPRO Digital Cameras – Tell your story.

#### **FEATURES:**

- 25X Optical Zoom
- 720p HD Video
- 16MP
- 24mm Wide Angle
- OIS (Optical Image Stabilization)
- 3" LCD
- AA Battery





## KODAK PIXPRO AZ251 DIGITAL CAMERA

SPECIFICATIONS	AZ251
Effective Image Sensor Pixels	16.15 Megapixels
Total Image Sensor Pixels	16.44 Megapixels [1/2.3" CCD]
Lens	ID.44 Megapixels [1/2.5 CCD]
Focal Length	4.3 mm (Wide) – 107.5 mm (Tele)
[ 35mm film equivalent ]	[24 mm (Wide) - 600 mm (Tele)]
Fnumber	F3.7 (Wide) – F6.2 (Tele)
Lens Construction	11 groups 12 elements
Optical Zoom	25×
Focusing Range	Normal: (Wide) 60 cm – $\infty$ , (Tele) 250 cm – $\infty$ Macro: 3 cm – $\infty$ (Wide Only)
Anti-Shake	Optical Image Stabilization
Digital Zoom	4x Digital Zoom (Combined Zoom: 100x)
Number of Recording Pixels	
Still Image	(4:3) 16MP: 4608x3456, 10MP: 3648x2736, 5MP: 2592x1944, 3MP: 2048x1536, 0.3MP: 640x480, (3:2) 14MP: 4608x3072, (16:9) 12MP: 4608x2592, 2MP: 1920x1080
Movie	1280x720(30/15fps), 640x480(30fps), 320x240(30fps)
Image Compression	Best, Fine, Normal
DCF, DPOF (Ver1.1) Support	Yes
File Format	
Still Image	Exif 2.3 (JPEG)
Movie	Movie Format: MOV (H.264), Audio: G.711 [Monaural]
Shooting Modes	Auto, P, S, A, M, Face Beautifier, Panorama, SCN [ASCN, Sport, Beach, Sunset, Fireworks, Night Landscape, Sketch, Snow, Children, ID, Glass, Photo Frame, Panning Shot, Portrait, Fish Eye, Party, Indoor, Leaf, Museum, Night Portrait, Pet (Dog), Pet (Cat)], Movie, CS, Landscape
Detection Features	Face, Smile, Blink, Cat, Dog
Photo Touch-up	Red-Eye Reduction, Skin Soften, Eye Brightening, Eye Enlargement, HDR
Panorama	0° - 180°
LCD Display	3.0 inch (230K Pixels)
ISO Sensitivity	Auto, ISO 80/100/200/400/800/1600/3200 (4M)
AF Method	Single AF, Multi-AF (TTL 9-point), Object Tracking, Face Detection
Exposure Metering Method	Artificial Intelligence AE (AiAE), Center-Weighted Average, Spot (Fixed to Center of Frame), Face AE
Exposure Control Method	Program AE (AE-Lock Available), Shutter Prior AE
Exposure Compensation	+/- 2EV in 1/3 Step Increments
Shutter Speed	1/2000 - 30 Seconds
Continuous Shooting	Yes
Playback Modes	Single Photo, Index (9/16 Thumbnails) Slide Show, Date, Zoom (Approx. x2 - x8)
White Balance Control	Auto (AWB), Daylight, Cloudy, Fluorescent, Fluorescent CWF, Incandescent, Manual, Color Temperature Setting (1900K - 10000K)
Flash	
Flash Method	Pop-up
Flash Modes	Auto, Red-Eye Reduction, Forced Flash, Slow Synchro, Red-Eye Reduction + Slow Synchro
Shooting Range	(Wide) Approx. 0.5 m - 7.1 m (ISO800); (Tele) Approx. 1.2 m - 4.2 m (ISO800)
Recording Media	Internal Memory: Approx. 8MB SD/SDHC Card (Up to 32GB Support) [MMC Card not supported]
Other Features	Eye-Fi, PictBridge, ExifPrint Support, Multi-Language Support (28 Languages)
Jacks	AV-OUT/USB 2.0 (Micro 5 pin USB), HDMI (Type D)
Power	AA Alkaline Battery (x4) AA NiMH Battery (x4) (Not Included)
Shooting Capability (Battery Performance)	Approx. 280 Shots of Alkaline Battery (Based on CIPA Standards) Approx. 500 Shots of AA NiMH Battery (Based on CIPA Standards)
Operation Environment	Temperature: 32° - 104°F / 0° - 40°C, Humidity: 0 - 90%
Dimensions (WxHxD)	Approx. 4.53 x 2.93 x 2.74 in. / 115.0 x 74.3 x 69.6 mm (Based on CIPA Standards)
Weight	Approx. 12.0oz. / 341g (Body Only)
Supplied Accessories	AA Alkaline Battery (x4), USB Cable, Neck Strap, Lens Cap, CD-ROM, Service Card, Quick Start Guide, Warranty Card

### JK Imaging Ltd.

17239 So. Main Street, Gardena, CA 90248 (888) 978-0806 To learn more about KODAK PIXPRO Digital Cameras: visit: **kodakpixpro.com** 

© 2018 JK Imaging, Ltd. The Kodak trademark, logo and trade dress are used under license from Eastman Kodak Company. All information contained in this document is subject to change without notice. Document Number/Sequence: U.DIS.0007.0218.en.02



