

KODAK PIXPRO FZ45

DIGITAL CAMERA



FZ45 FRIENDLY ZOOM

Introducing the FZ45, Friendly Zoom model from the KODAK PIXPRO collection of digital cameras. Compact, intuitive and oh so easy to use, the FZ45 is the perfect camera to take anywhere you go. One-touch video, red-eye removal, face detection and convenient AA batteries are just the start. KODAK PIXPRO Digital Cameras – Tell your story.

FEATURES:

- 4X Optical Zoom
- 27 mm Wide Angle
- 16 MP
- 2.7" LCD
- 1080p Full HD Video
- AA Batteries

4X
Optical
Zoom

27mm
WIDE

16MP

2.7" LCD

1080p
Full HD

Panorama
Capture



Available Colors:

● BLACK

● RED

○ WHITE

Images are simulated.



KODAK PIXPRO FZ45

DIGITAL CAMERA

SPECIFICATIONS	FZ45
Effective Image Sensor Pixels	16.35 Megapixels
Total Image Sensor Pixels	16.76 Megapixels [1/2.3"(CMOS)]
Lens	
Focal Length	4.9 mm (Wide) – 19.6 mm (Tele)
[35mm film equivalent]	[27 mm (Wide) – 108 mm (Tele)]
F number	F3.0 (Wide) – F6.6 (Tele)
Lens Construction	7 groups 7 elements
Optical Zoom	4x
Focusing Range	Normal: (Wide) 60cm – ∞, (Tele) 100 cm – ∞ Macro: 5 cm – ∞ (Wide Only)
Anti-Handshake	Digital Image Stabilization
Digital Zoom	6x Digital Zoom (Combined Zoom: 24x)
Number of Recording Pixels	
Still Image	(4:3) 16MP: 4608x3456, 10MP:3648x2736, 5MP: 2592x1944, 3MP: 2048x1536, 0.3MP: 640x480, (3:2) 14MP: 4608x3072, (16:9) 12MP: 4608x2592, 2MP: 1920x1080
Movie	1920x1080: 30fps, 1280x720: 60/30fps, 640x480: 30fps, High Speed Movie 640x480: 120fps
Image Compression	Best, Fine, Normal
File Format	
Still Image	Exif 2.3 (JPEG)
Movie	MOV [Image: Motion JPEG; Audio: Linear PCM (Monaural)]
Shooting Modes	M, P, Auto, Face Beautifier, Movie, Panorama, SCN
SCN Modes	ASCN, Landscape, Sport, Beach, Sunset, Fireworks, Night Landscape, Snow, Children, Portrait, Party, Night Portrait, Pet, Image Stabilization
Detection Features	Face, Smile, Blink, Cat, Dog
Photo Touch-up	Red-Eye Removal, Skin Soften, Eye Brightening, Eye Enlargement
HDR (High Dynamic Range)	Yes
Panorama Capture	0° – 180° (Horizontal)
LCD Display	2.7 inch (230K Pixels)
ISO Sensitivity	Auto, ISO 100/200/400/800/1600/3200
AF Method	Single AF, Multi-AF (TTL 9-point), Object Tracking, Face Detection
Exposure Metering Method	Artificial Intelligence AE (AiAE), Center-Weighted Average, Spot (Fixed to Center of Frame), Face AE
Exposure Control Method	Program AE (AE-Lock Available)
Exposure Compensation	+/- 3EV in 1/3 Step Increments
Shutter Speed	1/2000 – 4 Seconds (Manual: 30 Seconds)
Continuous Shooting	Yes
Playback Modes	Single Photo, Index (9/16 Thumbnails) Slide Show, Date, Zoom (Approx. x2 – x8)
White Balance Control	Auto (AWB), Daylight, Cloudy, Fluorescent, Fluorescent CWF, Incandescent, Manual, Color Temp. Setting (1900K-10000K)
Flash	
Flash Method	Internal
Flash Modes	Auto, Red-Eye Reduction, Fill Flash, Force Off, Slow Synchro, Red-Eye Reduction + Slow Synchro
Shooting Range	(Wide) Approx. 0.3 m – 5.2 m (ISO800); (Tele) Approx. 1.0 m – 2.4 m (ISO800)
Recording Media	Internal Memory: Approx. 63MB SD/SDHC/SDXC Card (Up to 512GB Support) [MMC Card Not Supported]
Other Features	Multi-Language Support (27 Languages)
Jacks	USB 2.0 (Micro 5-pin USB)
Power	AA Alkaline Battery (x2), AA NiMH Battery (x2) (Not Included)
Shooting Capability (Battery Performance)	Approx. 120 Shots of AA Alkaline Battery (Based on CIPA Standards) Approx. 1 hr for Video (@ 1080/30fps)
Operation Environment	Temperature: 32° – 104°F / 0° – 40°C, Humidity: 0 – 90%
Dimensions (WxHxD)	Approx. 3.66 x 2.37 x 1.12 in. / 93.0 x 60.2 x 28.7 mm (Based on CIPA Standards)
Weight	Approx. 4.1 oz. / 117g (Body Only)
Supplied Accessories	AA Alkaline Battery (x2), USB Cable, Wrist Strap, Service Card, Quick Start Guide, Warranty Card

JK Imaging Ltd.

17239 So. Main Street, Gardena, CA 90248
(888) 978-0806

© 2022 JK Imaging, Ltd. The Kodak trademark, logo and trade dress are used under license from Eastman Kodak Company.
All information contained in this document is subject to change without notice. Document Number/Sequence: US.DIS.0065.0322.en.01

To learn more about KODAK PIXPRO Digital Cameras:
visit: kodakpixpro.com

