# KODAK PIXPRO P1
DIGITAL CAMERA

## P1 FRIENDLY ZOOM

Capture every adventure with the new KODAK PIXPRO P1. Designed for life on the go, this compact and waterproof camera combines easy-to-use features and a convenient flip-up LCD screen for selfies. High-quality photo and video performance makes this camera the perfect companion for travel, outdoor activities, family fun, and everyday memories.

KODAK PIXPRO Digital Cameras - Tell Your Story.

### FEATURES:

- 13MP CMOS Sensor
- 26mm, F2.0 Fixed Focus Lens
- 2.8" (920K) 180° Tilt LCD
- Waterproof/Shockproof/Dustproof
- 3 color Ring Light
- 1080p Full HD Video
- Built-in Li-ion Battery

Available Colors:

- GUNMETAL/BLACK
- GUNMETAL/WHITE
- AQUA/WHITE

**13MP BSI CMOS** | **5m/16FT Waterproof** | **1m/3FT Shockproof** | **Fill Light RING** | **Full HD** | **Lithium-ion Battery**

# KODAK PIXPRO P1
## DIGITAL CAMERA

| SPECIFICATIONS | P1 |
|---|---|
| Effective Image Sensor Pixels | 13 Megapixels |
| Total Image Sensor Pixels | 13 Megapixels [1/3" BSI CMOS] |
| Lens | |
| Focal Length | 3.57 mm |
| [ 35mm film equivalent ] | 26 mm |
| F number | F2.0 |
| Lens Construction | 5 elements |
| Optical Zoom | Fix Focus |
| Focusing Range | Normal: 60 cm — ∞<br>Macro: 8 cm — ∞ |
| Autofocus System | TTL Autofocus |
| Digital Zoom | 4x Digital Zoom |
| Number of Recording Pixels | |
| Still Image | (4:3) 13MP: 4160x3120, 5MP: 2592x1944, (16:9) 10MP: 4160x2340, 2MP: 1920x1080 |
| Movie | 1920x1080: 60fps / 30fps, 1280x720: 60fps / 30fps |
| Image Compression | Best, Fine |
| DCF Support | Yes |
| File Format | |
| Still Image | Exif 2.2 (JPEG) |
| Movie | MOV [Image: H.264; Audio: Linear PCM (Monaural)] |
| Shooting Modes | Auto, P, Portrait, Night, Landscape, Movie, Backlight, Beach, Children, Underwater |
| Waterproof | Up to 5m |
| Shockproof | Up to 1m |
| Dustproof | Equivalent to JIS/IEC (IP6X) |
| LCD Display | 2.8 inch (920k Pixels) |
| Touch Panel | No |
| Angle Adjustment | Tilt (upwards approx. 180°) |
| G-Sensor | Yes |
| ISO Sensitivity | Auto ISO 100/200/400/800/1600 |
| AF Method | Single AF |
| Exposure Metering Method | Average Metering, Spot (Fixed to Center of Frame), Center-Weighted Metering |
| Exposure Control Method | Program AE (AE-Lock Available) |
| Exposure Compensation | +/- 2EV in 1/3 Step Increments |
| Shutter Speed | 1/10000 ~ 2 Seconds |
| Continuous Shooting | Yes |
| Playback Modes | Single, Index (9 Thumbnails), Zoom (Approx. ×2 ~ ×4) |
| White Balance Control | Auto (AWB), Daylight, Cloudy, Fluorescent, Fluorescent CWF, Incandescent, Underwater |
| LED Flash | |
| Flash Method | Internal |
| Flash Modes | Flash Auto, Force Flash, Force Off |
| Fill Light Ring | Cool White Light (7100K), White Light (5300K), Warm Light (2500K) |
| Recording Media | microSD/microSDHC/microSDXC Card (Up to 1.5TB Support) [MMC Card Not Supported] |
| Mulit-Language Support (27) | English, Chinese (Simplified and Traditional), Japanese, Korean, French, Spanish, Portuguese, Thai, Indonesia, Vietnamese, Italian, German, Dutch, Russian, Polish, Swedish, Danish, Finnish, Norwegian, Greek, Turkish, Hungarian, Croatian, Czech, Arabic, Hindi |
| Jacks | USB 2.0 (Type-C) |
| Power | Built-in Li-ion Battery, 3.7V 700mAh, In-Camera Charging |
| Battery Charging Time | Approx. 2.5 Hours (Use AC Adapter and Battery is Exhausted) |
| Shooting Capability (Battery Performance) | Approx. 200 Shots (Based on CIPA Standards)<br>Approx. 1h 30min for Video (@1080/30fps) |
| Operation Environment | Temperature: 32° – 104°F / 0° – 40°C, Humidity: 0 – 90% |
| Dimensions (WxHxD) | Approx. 4.15 × 24.8 × 0.89 in. / 105.5× 63 × 22.5mm (Based on CIPA Standards) |
| Weight | Approx. 4.76 oz. / 135g (Body Only) |
| Supplied Accessories | Type-C USB Cable, AC Adapter, Wrist Strap, Quick Start Guide, Warranty Card, Service card |

[1] Use Class 10 Card or Better
[2] SPEC For US


**JK Imaging Ltd.**

14067 Stage Road, Santa Fe Springs, CA 90670
(888) 978-0806


To learn more about KODAK PIXPRO Digital Cameras:
visit: **kodakpixpro.com**


© 2026 JK Imaging, Ltd. The Kodak trademark, logo and trade dress are used under license from Eastman Kodak Company.
All information contained in this document is subject to change without notice. Document Number/Sequence: U.DIS.20260608.en.01