

S-1 COMPACT SYSTEM

Great things do come in small packages. Meet the KODAK PIXPRO S-1 Compact System Camera and unleash your creativity. This powerful, micro-four thirds model features a slim body and design with an interchangeable lens and manual focus. A 16MP CMOS sensor and 1080p HD video produce crystal clear images with razor sharp detail. Wireless connectivity, 4 fps multi-burst and a large 3" articulating LCD are just a few of the features that set this camera apart from the rest. KODAK PIXPRO Digital Cameras – Tell your story.

FEATURES:

- 16MP CMOS Sensor
- Full HD 1080p Video
- 4 fps Multi-Burst Shooting
- Sensor Shift Optical Image Stabilization
- · RAW and JPEG Formats
- 3" Articulating LCD
- · Wi-Fi Connection
- Wirelessly Connect / Control with your iOS™/Android™ Device















Available Colors:



BLACK







KODAK PIXPRO S-1

DIGITAL CAMERA

| SPECIFICATIONS | \$-1 |
|--|--|
| Effective Image Sensor Pixels | 16.83 Megapixels |
| Image Sensor Size | 17.3 mm x 13 mm |
| Lens Mount | Micro Four Thirds Mount |
| Anti-Handshake | Sensor Shift Optical Image Stabilization |
| Number of Recording Pixels | |
| Still Image | (4:3) 16MP: 4640x3480, 10MP: 3648x2736, 4MP: 2336x1752, 3MP: 2048x1536, 0.3MP: 640x480, (3:2) 14MP: 4608x3072, (16:9) 12MP: 4608x2592, 2MP: 1920x1080 |
| Movie | (Full HD) 1920x1080-30fps, (HD) 1280x720-60fps, 1280x720-30fps, (VGA) 640x480-30fps High-Speed Movie: VGA (120 fps) |
| Digial Zoom | 2x, 4x |
| File System | DCF 1.0, DPOF, Exif 2.3, PictBridge |
| File Format | |
| Still Image | JPEG (Fine, Standard), RAW, RAW+ JPEG (Fine) |
| Movie | MOV (H.264), Audio: Linear PCM [Stereo] |
| Shooting Modes SCN Modes | Auto, P, S, A, M Panorama, Face Beautifier, Sport, Fireworks, Children, Sunset, Landscape, Night Portrait, Pet, Multi Exposure, Handheld Night, Snow, Party, Portrait], Wi-Fi, CS, Movie |
| Scan Panorama | Up to 360° |
| LCD Display | 3.0 inch (920K Pixels), Articulating Screen (max. 90° upward / 45° downward) |
| ISO Sensitivity | Auto, ISO 200/400/800/1600/3200/6400/12800 |
| Focus Modes | Single AF, Continuous AF, Manual Focus, Manual Focus + Single AF |
| Focus Area Selection | 1-Area-Focusing, 25-Area-Focusing, Face Detection, Manual Area Focusing |
| AE/AF Lock | Yes |
| AF Assist Lamp | Yes |
| Exposure Modes | Artificial Intelligence AE (AiAE), Center-Weighted Average, Spot, Multi-spot, Face AE, Program AE (AE-Lock Available), Aperture Priority AE, Shutter Priority AE, Manual |
| Metering Range | EV 0-16 (F3.5, ISO 200) |
| AE Bracket | Manual: + 3 Stops in 1/3 Stop Increments |
| | AEB: + 2 Stops in 1/3 Stop Increments |
| Exposure Compensation | + 3 EV in 1/3 Step Increments |
| Shutter Type | Mechanical, Electronically-Controlled, Focal-Plane Shutter |
| Shutter Speed | 1/4000 - 30 Seconds (Manual: 30 Minutes) |
| Continuous Shooting | Approx. 4fps (Full Resolution) |
| Playback Modes | Single Photo, Index, (9/16 Thumbnails), Date, Burst Shooting, Zoom (Approx, x2 - x8), Slide Show (Still/Movie/Still+Movie) |
| White Balance Control | Auto (AWB), Daylight, Shadow, Cloudy, Fluorescent, Fluorescent CWF, Incandescent, Manual, WB Bracket, Color Temperature Setting (1900K - 10000K) |
| Flash | External |
| Flash Modes | Auto, Red-Eye Reduction, Fill Flash, Flash Off, Slow Sync, Rear Curtain Sync, Slow Sync + Red-Eye Reduction |
| Guide No. | 6.8, ISO 100 • m |
| Filter | Normal, Black and White, Vivid, Vignetting, Sketch, Dreamy, Fish Eye, Punk, Salon, Kodachrome, Ektachrome, Kodacolor, Negative, Reflection, 4 Grids - Stylish, 4 Grids - Partial Color |
| Other Features | Wi-Fi (802.11 b/g/n), Eye-Fi [®] Compatible, Multi-Language Support (27 Languages) |
| Jacks | AV-OUT/USB 2.0 (Micro 5 pin USB), HDMI, (Type D), Hot Shoe |
| Power | Rechargeable Li-ion Battery LB-070, 7.4V 1000mAh, In-Camera Charging |
| Shooting Capability (Battery Performance) | Approx. 410 Shots (Based on CIPA Standards) |
| Operation Environment | Temperature: 8° – 104°F / 0° – 40°C, Humidity: 0 – 90% |
| Dimensions (WxHxD) | Approx. 4.55 x 2.66 x 1.40 in / 115.7 x 67.4 x 35.6 mm (Based on CIPA Standards) |
| Weight | Approx. 10.2 oz. / 290g (Body Only) |
| Standard Accessories | KODAK PIXPRO SZ ED 12-45mm F3.5-6.3 AF Lens Unit, Rechargeable Li-ion Battery LB-070, P10 Flash Unit, AC Adapter, USB Cable, Neck Strap, CD-ROM, Service Card, Warranty Card, Manual |

JK Imaging Ltd.

17239 So. Main Street, Gardena, CA 90248 (888) 978-0806

© 2018 JK Imaging, Ltd. The Kodak trademark, logo and trade dress are used under license from Eastman Kodak Company. All information contained in this document is subject to change without notice. Document Number/Sequence: U.DIS.0013.1217.en.06

To learn more about KODAK PIXPRO Digital Cameras:

visit: kodakpixpro.com











